

# Outside Plant

## Toby Joint Box - D400 Carriageway - Badged CATV

VM SKU 10015690



Up to  
D400



### Description

The Toby Joint Box provides a compact and secure environment for quick and easy connections into below ground fibre networks.

The system consists of a ductile iron surface box sitting on compact, stackable chamber rings. High strength yet light weight design, specifically engineered for use in the carriageway when the footpath is congested.

The Toby Joint Box is suitable for new or retrofit installations and can be easily drilled to suit on-site conditions.

#### System Components:

- 2 No. Toby Joint Box Stackable Rings
- 1 No. D400 Ductile Surface Box Cover

### BENEFITS

- Surface box is tested and approved to BS5834 Grade A
- Heavy duty
- Ideal for EN124 carriageway Group 4 installations.
- Fast & easy installation
- Badged CATV
- Stackable sections to increase depth

### Dimensions

	Clear opening size (mm)	Overall size (mm)	Depth (mm)	Weight (kg)
Toby Joint Box - Ring	150 x 150	240x240	Stackable 150mm rings, clip together.	1.8

	Clear opening size (mm)	Overall frame size (mm)	Frame Depth (mm)	Weight (kg)
D400 CATV Cover	150 x 150	230 x 230	100	8.5

### Technical

- Ductile Iron lid grade 500/7 according to BS 1563:2011
- Surface boxes are third party certified by BSI and kite marked to the requirements of BS 5834 Grade A Part 2
- The Toby Joint Box rings are moulded from recycled Polypropylene (PP) with excellent strength to weight properties. Each section is manufactured with twinwall and internal ribbing for improved loading performance.
- Operating Temperature: -45° to 90° C

