

Access Covers & Frames



RADIUS
CTS

Concrete Covers



openreach
APPROVED

Description

Radius high quality concrete infill cover with fabricated steel frame.

- The frames, covers and cross pieces are manufactured from rolled steel to BS 1449 and galvanised to BS EN ISO 1461
- Manufactured to BS EN 124 rating B 125
- BSI Kitemark
- openreach approved
- Installation area: Group 2 - Footways, pedestrians areas and comparable areas, car parks or car parking decks, and lower groups
- Customer badging available on request

FEATURES

- anti-slip concrete
- resistant to chemicals, deformation, rust and corrosion
- no inherent scrap value
- locking and badging option

Technical Features

EN Reference	To Suit Chamber Clear Opening (mm)	No. of Covers per Chamber	Approx. External Dimension (mm)	Combined Weight (kg)	Pallet Qty.	Openreach approval
EN7	300 × 300	1	390 × 390	20	40	N/A
EN55	450 × 300	1	540 × 390	30	30	N/A
EN1	600 × 450	1	690 × 540	48	20	N/A
EN2	725 × 255	1	815 × 345	38	24	Y
EN4	915 × 445	1	1005 × 540	72	16	Y
EN5	610 × 610	1	710 × 710	66	16	Y
EN6	1310 × 610	2	1400 × 704	134	10	Y
EN10	2320 × 750	3	2410 × 833	276	1	Y

